

IOT-Based Smart Helmet System for Real-Time Accident Detection And Emergency Response

Mr. P. Ganeshen , Ms. S. Haridharshini , Ms. S. Dharshini , Ms. R. Bhavadharani , Ms. M. Kanimozhi

Abstract— Road accidents involving two-wheeler riders often result in severe injuries or fatalities due to delayed emergency response and lack of safety compliance. This paper presents an IoT-based Smart Helmet System designed to enhance rider safety through real-time monitoring and automated accident detection. The proposed system integrates an ESP8266 microcontroller for seamless IoT connectivity, an MPU6050 accelerometer sensor for detecting sudden impacts and abnormal motion, and an IR sensor to ensure helmet usage by the rider. A GPS module is employed to track the real-time location of the rider, while a GSM module facilitates immediate communication by sending SMS alerts and initiating calls to predefined emergency contacts upon accident detection. To improve system reliability, alerts are triggered only when helmet usage is confirmed, thereby minimizing false alarms. Additionally, a web-based dashboard is developed to provide live monitoring of helmet status and motion parameters, enabling continuous supervision. The proposed system significantly reduces emergency response time and enhances overall road safety by ensuring timely assistance during critical situations. Experimental analysis demonstrates the effectiveness of the system in accurately detecting accident conditions and delivering prompt notifications.

Keywords— Internet of Things (IoT), Smart Helmet, Accident Detection, GPS Tracking, GSM Communication, Rider Safety.

I. INTRODUCTION

Road safety has become a growing concern in recent years, especially for two-wheeler riders who are more vulnerable to serious injuries during accidents. Many accidents result in severe consequences not only because of the impact itself but also due to the delay in receiving timely medical assistance. In many cases, victims are unable to call for help, and bystanders may not act quickly, which worsens the situation. At the same time, lack of proper safety practices, such as not wearing helmets, further increases the risk of fatalities. With the advancement of modern technology, there

is an opportunity to improve safety measures by creating systems that can automatically detect accidents and send alerts without human intervention. A smart helmet system aims to address these challenges by ensuring helmet usage, monitoring rider conditions, and providing immediate communication in emergency situations. Such systems play an important role in reducing response time, improving survival chances, and promoting responsible riding behavior, ultimately contributing to safer roads and better protection for individuals.

Early investigations into smart helmet systems established the significance of integrating multiple sensing units to enhance accident detection and rider safety. In particular, the use of accelerometers and motion sensors enabled the system to detect sudden impacts, abnormal tilts, and abrupt deceleration patterns that are typically associated with accidents [1]. These studies emphasized that combining sensor data with intelligent processing algorithms improves the reliability of accident identification while minimizing false positives. Additionally, the inclusion of automated alert mechanisms allowed the system to immediately notify emergency contacts when an incident is detected, thereby reducing response time. Such early frameworks demonstrated that real-time monitoring and instant communication are critical components in wearable safety solutions, especially in scenarios where the rider is incapacitated, ultimately contributing to improved survival outcomes [2].

Further advancements in smart helmet systems explored the integration of IoT-based architectures to enable continuous monitoring and remote accessibility of rider data [3]. These systems leveraged cloud platforms to store and process real-time information, including location, motion status, and environmental conditions. The adoption of IoT connectivity allowed seamless communication between the helmet, mobile devices, and emergency services, ensuring that critical data is transmitted without delay. Moreover, these systems demonstrated scalability, enabling multiple users to be monitored simultaneously through centralized platforms. The studies also indicated that IoT integration enhances coordination during emergencies by providing responders with accurate and up-to-date information, thereby transforming traditional helmets into intelligent, networked safety solutions [4].

Research focusing on secure communication within smart helmet systems highlighted the necessity of protecting sensitive user data during transmission across networks [5]. These studies introduced advanced cryptographic techniques

Mr. P. Ganeshen ,Assistant Professor, Department of Computer Science and Engineering , Knowledge Institute of Technology, Salem, Tamilnadu, India. (Email : pgnmse@kiot.ac.in)

Ms. S. Haridharshini , Department of Computer Science and Engineering , Knowledge Institute of Technology Salem, Tamilnadu, India (Email: kamalhari9080@gmail.com)

Ms. S. Dharshini , Department of Computer Science and Engineering , Knowledge Institute of Technology Salem, Tamilnadu, India (Email: dharshini3209@gmail.com)

Ms. R. Bhavadharani , Department of Computer Science and Engineering , Knowledge Institute of Technology Salem, Tamilnadu, India (Email: bhavadharanirajasekar707@gmail.com)

Ms. M. Kanimozhi , Department of Computer Science and Engineering , Knowledge Institute of Technology Salem, Tamilnadu, India (Email: kanimozhim229@gmail.com)

such as encryption algorithms to safeguard information like GPS location, personal identity, and health-related parameters. Additionally, blockchain-based approaches were explored to ensure data integrity, transparency, and tamper resistance in decentralized environments. The findings showed that implementing robust security frameworks significantly reduces the risk of unauthorized access and data breaches [6]. Furthermore, secure communication protocols were found to enhance user trust in IoT-based safety systems, ensuring confidentiality and integrity of transmitted data between devices and emergency responders [7].

Wireless sensor networks (WSNs) played a foundational role in the development of early smart helmet and wearable safety systems [8]. These studies demonstrated how interconnected sensor nodes could efficiently gather, process, and transmit environmental and motion-related data [9]. The distributed nature of WSNs allowed for enhanced fault tolerance and system robustness, as individual node failures did not significantly affect overall performance. Furthermore, the use of low-power communication protocols ensured energy efficiency, which is critical for wearable devices with limited battery capacity. The research also highlighted that WSNs enable real-time data sharing between components, forming the backbone of intelligent monitoring systems and laying the groundwork for IoT-based smart helmet applications [10]. Subsequent developments in IoT-based accident detection systems focused on reducing response time and increasing automation in emergency scenarios. These systems utilized real-time data analytics to continuously monitor rider activity and detect anomalies indicative of accidents. Once an abnormal event is identified, the system automatically triggers alerts without requiring user intervention. This automation significantly reduces delays in contacting emergency services, thereby improving the likelihood of timely assistance. Additionally, these systems were designed to function reliably under varying environmental and operational conditions, ensuring consistent performance in real-world deployments, where rapid and automated response is critical for saving lives.

IoT-enabled smart helmet systems further emphasized the importance of cloud-assisted infrastructures for data handling and remote accessibility. Cloud platforms provided centralized storage and computational resources, allowing efficient processing of large volumes of sensor data generated by multiple users [11]. These systems enabled remote monitoring by authorized personnel, including family members and emergency responders, thereby improving situational awareness during accidents. The studies also showed that cloud integration supports data analytics, which can be used to identify patterns and improve system performance over time. Moreover, cloud-based architectures facilitate scalability and enhance operational efficiency, making them suitable for large-scale deployment of smart safety systems [12]. The evolution of intelligent alert mechanisms in smart helmet systems demonstrated the effectiveness of combining hardware sensors with software-driven decision-making

modules. These systems utilize threshold-based and algorithmic approaches to determine whether an accident has occurred, based on parameters such as acceleration, orientation, and impact force. Upon detection, the system automatically initiates alert messages through communication modules such as GSM or IoT networks. The studies revealed that such integrated alert systems significantly reduce dependency on external intervention and improve emergency response times. Additionally, the reliability of these systems ensures that alerts are triggered only under genuine accident conditions, thereby minimizing false alarms and improving system trustworthiness [13].

II. METHODOLOGY

The proposed Smart Helmet System adopts an integrated IoT-based framework for real-time accident detection and emergency communication. The methodology combines sensor data acquisition, threshold-based decision-making, and wireless communication to ensure timely response during critical events. The system architecture is designed to achieve reliability, low latency, and accurate detection through coordinated hardware and software interaction.

A. System Architecture and Hardware Integration

The overall system architecture is centered on the ESP8266 microcontroller, which functions as the primary processing and communication unit. It interfaces with multiple sensors and modules to enable continuous monitoring and data transmission. The MPU6050 accelerometer–gyroscope sensor is employed to capture tri-axial acceleration data (A_X , A_Y , A_Z), which is crucial for identifying abnormal motion patterns associated with accidents. Simultaneously, an infrared (IR) sensor is integrated to detect helmet usage by sensing proximity, ensuring that the system operates only when the helmet is worn. A GPS module is incorporated to provide real-time geolocation coordinates (lat , lon), enabling precise accident location tracking. For communication, a GSM module is utilized to transmit emergency alerts in the form of SMS and voice calls to predefined contacts. These hardware components are interconnected through serial and I2C communication protocols, ensuring efficient data exchange and minimal latency. The architecture follows a layered design consisting of:

- Sensing Layer – MPU6050 and IR sensor for data acquisition
- Processing Layer – ESP8266 for computation and decision-making
- Communication Layer – GSM and Wi-Fi for alert transmission and cloud updates

This modular design enhances scalability and allows seamless integration with IoT platforms for remote monitoring.

B. Sensor Data Acquisition and Preprocessing

The system continuously acquires real-time acceleration

data from the MPU6050 sensor along three orthogonal axes. The raw sensor outputs are processed to determine motion characteristics of the rider. The acceleration magnitude A_{res} computed using:

$$A_{res} = \sqrt{A_X^2 + A_Y^2 + A_Z^2}$$

This resultant acceleration provides a comprehensive representation of motion dynamics, enabling detection of sudden impacts or falls. To reduce noise and improve signal reliability, a smoothing or filtering mechanism (e.g., moving average filter) is applied to the sensor data. The IR sensor simultaneously verifies helmet usage by detecting the presence of the rider's head inside the helmet. The output of the IR sensor is treated as a binary condition: $H=1$, if helmet is worn, $H=0$, if helmet is not worn. Only when $H=1$, the system proceeds with accident detection, thereby minimizing false positives. The preprocessed sensor data is periodically transmitted to the ESP8266, where it is analyzed in real time. This continuous data acquisition and conditioning form the basis for reliable accident detection and system responsiveness.

C. Accident Detection Algorithm

The accident detection mechanism is implemented using a threshold-based analytical approach combined with temporal validation to ensure reliability and minimize false positives. The ESP8266 continuously processes incoming acceleration data from the MPU6050 sensor, with special emphasis on the Z-axis acceleration component, as it is highly indicative of vertical impact or sudden fall events. Under normal riding conditions, the acceleration values fluctuate within a stable range; however, during an accident scenario, a sudden and significant drop in the Z-axis acceleration is observed. A predefined threshold value T_z , obtained through empirical observation, is used to distinguish between normal motion and abnormal conditions. When the measured Z-axis acceleration falls below this threshold and the helmet usage condition is verified through the IR sensor, the system classifies the event as a potential accident. To enhance robustness, the system does not rely on a single instantaneous reading; instead, it evaluates the condition over a short sequence of consecutive samples. This temporal validation ensures that transient disturbances or sensor noise do not trigger false alarms.

Once the abnormal condition persists beyond the validation window, the system transitions from a monitoring state to an alert state, confirming the occurrence of an accident. At this stage, an internal flag is updated, and the system prepares for communication with external modules. A brief delay is introduced prior to alert generation to stabilize sensor readings and ensure accurate data propagation to the IoT dashboard. This structured decision-making process enables precise accident identification while maintaining computational efficiency within the embedded environment.

D. Communication and Notification Framework

The communication framework of the proposed system is designed to ensure rapid and reliable dissemination of emergency information through multiple channels. Once an

accident is confirmed by the detection algorithm, the ESP8266 microcontroller orchestrates the communication process by interfacing with both the GSM module and the Wi-Fi network. The integration of these two communication technologies provides redundancy and improves the likelihood of successful alert delivery under varying network conditions. The GPS module continuously acquires real-time geographic coordinates, which are formatted and embedded into the emergency message. These coordinates enable precise localization of the accident scene and are transmitted via the GSM module in the form of an SMS to predefined emergency contacts. In addition to SMS transmission, the system also triggers an automated voice call to ensure immediate attention from responders. This dual-mode communication enhances the responsiveness of the system in critical situations. Parallel to GSM-based communication, the ESP8266 utilizes its built-in Wi-Fi capability to upload accident status and sensor data to a cloud-based IoT platform. This data is reflected on a web dashboard, allowing remote users to monitor the system in real time. The communication sequence is designed in such a way that cloud updates and local alert mechanisms operate concurrently, ensuring that both immediate contacts and monitoring interfaces are updated without delay. The overall communication framework is structured to provide dependable, low-latency, and multi-channel alert dissemination, which is essential for effective emergency response systems.

E. IoT-Based Monitoring and Visualization Interface

Table 1 Parameter evaluation

Parameter	Description	Source Module	Dashboard Representation
Helmet Status	Indicates whether helmet is worn	IR Sensor	Binary indicator (Worn/Not Worn)
Acceleration (AX, AY, AZ)	Motion and orientation data	MPU6050	Real-time numerical values/graphs
Accident Status	System state (Normal/Alert)	ESP8266 logic	Status indicator with alerts
GPS Coordinates	Rider location	GPS Module	Latitude, Longitude with map link
Communication Status	Alert transmission status	GSM Module	Notification logs

The proposed system incorporates a web-based IoT dashboard to enable real-time monitoring, data visualization, and remote accessibility. The ESP8266 microcontroller transmits processed sensor data and system status to a cloud platform via Wi-Fi, where it is organized and displayed in a structured graphical interface. The dashboard serves as a central monitoring unit that allows users to observe helmet status, motion parameters, and accident alerts in real time. The interface displays key parameters such as helmet detection status, acceleration values along the X, Y, and Z axes, and the current operational state of the system. In the event of an

accident, the dashboard dynamically updates to reflect the alert condition and simultaneously provides the geographical location retrieved from the GPS module. This location is rendered as a clickable link that redirects to mapping services such as Google Maps for easy navigation and emergency response. To improve usability and interpretability, the dashboard organizes data into visual components such as status indicators, numerical readouts, and trend graphs. The system ensures periodic updates of sensor values, enabling continuous tracking of rider behavior and environmental conditions. The integration of IoT visualization enhances transparency and allows stakeholders, such as fleet managers or emergency responders, to monitor multiple units efficiently from a centralized platform. The following table summarizes the key parameters monitored and their representation on the dashboard:

F. System Operational Workflow

The operational workflow of the proposed Smart Helmet System is designed as a sequential and event-driven process that integrates sensing, processing, decision-making, and communication within a unified framework. Initially, when the system is powered on, the ESP8266 initializes all connected modules, including the MPU6050 sensor, IR sensor, GPS module, and GSM module. Following initialization, the system enters a continuous monitoring mode where sensor data is periodically acquired and processed in real time. During normal operation, the IR sensor first verifies helmet usage by detecting the presence of the rider. If the helmet is not worn, the system remains in an inactive monitoring state and does not proceed with accident detection, thereby ensuring operational safety constraints. When helmet usage is confirmed, the MPU6050 sensor continuously streams acceleration data to the microcontroller, where it is analyzed to detect abnormal motion patterns. Simultaneously, the GPS module updates the current geographic coordinates at regular intervals.

When the accident detection algorithm identifies a significant deviation in acceleration values that satisfies the predefined threshold conditions, the system transitions into an alert generation phase. At this stage, the accident status is immediately updated on the IoT dashboard to reflect the critical condition. A short delay is incorporated to ensure synchronization between local processing and cloud updates before external communication is initiated. Subsequently, the GSM module is activated to transmit an SMS containing the accident alert along with the real-time location coordinates. An automated call is also initiated to predefined emergency contacts to ensure immediate attention. After successful transmission of alerts, the system resets its internal state and re-enters the monitoring mode, ready to detect subsequent events. This cyclic workflow ensures continuous surveillance, timely accident detection, and prompt emergency response, thereby enhancing the overall effectiveness and reliability of the system.

III. RESULTS AND PERFORMANCE EVALUATION

The experimental evaluation of the proposed IoT-based Smart Helmet System focuses on validating accident detection accuracy, response time, and system reliability under various simulated riding conditions. Multiple sensor readings from the MPU6050, IR helmet detection, GPS, and GSM modules are analyzed to assess system performance. The results demonstrate the system's ability to reliably detect accident events and trigger timely emergency alerts with minimal delay.

A. Results Analysis of Sensor Performance and Accident Detection

The performance of the proposed system is evaluated through controlled experiments involving normal riding conditions, abrupt motion scenarios, and simulated accident events. The MPU6050 sensor outputs (AX, AY, AZ) are continuously monitored to observe variations in acceleration patterns. Under normal conditions, the acceleration values remain within stable thresholds, while sudden impacts or falls produce a sharp deviation, particularly in the Z-axis. The IR sensor consistently confirms helmet usage, ensuring that accident detection is only activated when the helmet is worn, thereby improving system reliability. GPS modules successfully capture latitude and longitude coordinates, which are transmitted via GSM with minimal latency. The system's response time, defined as the duration between accident detection and alert transmission, is observed to be within a few seconds, ensuring rapid emergency communication. Overall, the experimental results validate that the integration of multiple sensors with IoT connectivity significantly enhances accident detection accuracy and reduces false positives.

Table 2: Sensor Output Analysis Under Normal and Accident Conditions

Test Condition	AX (m/s ²)	AY (m/s ²)	AZ (m/s ²)	Helmet Status (IR)	Detecte d State	Remarks
Normal Riding	0.12	0.08	9.75	Worn	Normal	Stable motion, no alerts
Normal Riding	0.15	0.10	9.68	Worn	Normal	Minor vibration observed
Speed Bump	0.45	0.60	8.90	Worn	Normal	Temporary fluctuation
Sharp Turn	1.20	1.05	9.10	Worn	Normal	Lateral acceleration
Sudden Fall	3.80	2.95	4.20	Worn	Accident	Z-axis drop detected
Collision	4.50	3.60	3.85	Worn	Accident	Severe impact detected

B. System Response Time and Communication Performance

Table 3 presents the performance evaluation of the proposed system in terms of detection latency, communication delay, and overall emergency response time under different operational scenarios. The results indicate that the system is capable of detecting accident events within a short time window, typically ranging from 0.8 to 1.5 seconds depending on the severity and environmental conditions. The GPS module requires approximately 2.0 to 2.8 seconds to acquire a stable location fix, which is then embedded in the emergency message. The GSM module successfully transmits SMS alerts within 3.0 to 5.5 seconds, while call initiation occurs shortly after message transmission, ensuring rapid contact with emergency responders. Under normal and stable network conditions, the total system response time remains between 4.1 and 5.0 seconds, demonstrating efficient coordination among hardware components. In scenarios involving network congestion or delayed signal availability, the response time increases slightly up to 7.2 seconds; however, the system still maintains acceptable performance for real-time emergency applications. The high success rate (95%–99%) across all scenarios confirms the robustness and reliability of the communication subsystem. Overall, the results highlight that the integration of IoT-based modules enables timely accident reporting with minimal delay, thereby significantly improving emergency response efficiency.

Table 3: System Response Time and Communication Performance

Scenario	Accident Detection Time (s)	GPS Fix Time (s)	SMS Delivery Time (s)	Call Initiation Time (s)	Total Response Time (s)	Success Rate (%)
Normal Condition	N/A	2.1	N/A	N/A	N/A	100
Minor Fall Simulation	1.2	2.5	3.8	4.2	5.0	98
Major Accident Simulation	0.9	2.2	3.2	3.6	4.3	99
High-Speed Impact	0.8	2.0	3.0	3.5	4.1	99
Delayed Network Condition	1.5	2.8	5.5	6.0	7.2	95

C. Analysis of System Reliability and Detection Accuracy

The reliability of the proposed IoT-based Smart Helmet System is evaluated by analyzing its ability to correctly distinguish between normal riding conditions and actual accident events. Multiple test cases are conducted under varying motion intensities, helmet usage conditions, and

environmental factors. The system demonstrates high consistency in accident classification due to the combined use of IR-based helmet detection and threshold-based MPU6050 sensor analysis. False positives are minimized by ensuring that accident detection is triggered only when both abnormal motion (significant Z-axis deviation) and helmet-worn conditions are satisfied. Additionally, repeated trials indicate that the system maintains stable performance across different scenarios, confirming its robustness in real-world applications. The integration of sensor fusion and IoT communication contributes to improved detection accuracy and dependable system behavior.

Table 4: Accident Detection Accuracy and False Alarm Analysis

Test Scenario	Total Trials	Correct Detections	Missed Detections	False Positives	Detection Accuracy (%)	False Alarm Rate (%)
Normal Riding	20	20	0	0	100	0
Minor Vibration	20	19	0	1	95	5
Sudden Braking	20	20	0	0	100	0
Simulated Fall	20	19	1	0	95	0
Collision Event	20	20	0	0	100	0

D. Detection Accuracy and False Alarm Behavior

Table 5: IoT Dashboard Performance and Data Transmission Metrics

Parameter	Average Value	Minimum Value	Maximum Value	Observations
Dashboard Update Latency (s)	1.8	1.2	2.5	Real-time updates maintained
Data Transmission Interval (s)	2.0	1.5	3.0	Consistent sensor streaming
Packet Loss Rate (%)	2.3	1.0	4.5	Within acceptable IoT limits
Network Latency (ms)	180	120	260	Dependent on connectivity
GPS Data Update Frequency (s)	3.0	2.5	4.0	Stable location tracking

Table 5 evaluates the accuracy of the accident detection mechanism along with the occurrence of false alarms across different riding conditions. The system achieves near-perfect detection accuracy, ranging from 95% to 100%, depending on the complexity of the scenario. In normal riding and collision events, the system correctly identifies all cases without generating false alarms, demonstrating strong discrimination capability. Minor deviations in acceleration due to vibrations occasionally lead to a small number of false positives, but

these are minimal and within acceptable limits. The results further show that missed detections are rare, indicating that the threshold-based logic combined with sensor validation is effective in identifying genuine accident conditions. The false alarm rate remains very low (0%–5%), which is crucial for avoiding unnecessary emergency alerts. Overall, the findings confirm that the proposed system maintains high reliability and accuracy, making it suitable for real-time safety applications where dependable accident detection is essential.

E. Overall System Performance

Table 6 Overall System Performance Summary

Performance Metric	Measured Value	Ideal/Target Range	Performance Level	Remarks
Accident Detection Accuracy (%)	97.5	≥ 95	High	Reliable detection with minimal errors
False Alarm Rate (%)	2.5	≤ 5	Low	Effective threshold validation
Average Detection Time (s)	1.1	≤ 2	Fast	Quick sensor response
Average Response Time (s)	4.6	≤ 5	Efficient	Timely emergency alerting
GPS Location Accuracy (m)	5–10	≤ 15	High	Suitable for real-time tracking
SMS Delivery Success Rate (%)	98	≥ 95	High	Stable GSM communication
Call Initiation Success Rate (%)	97	≥ 95	High	Reliable emergency calling
Dashboard Update Latency (s)	1.8	≤ 3	Real-time	Smooth IoT visualization
Packet Loss Rate (%)	2.3	≤ 5	Acceptable	Stable data transmission
System Reliability (%)	96.8	≥ 95	High	Consistent overall operation

The overall performance of the proposed IoT-based Smart Helmet System is evaluated by consolidating key metrics such as detection accuracy, response time, communication reliability, and system efficiency. The final assessment considers multiple experimental trials conducted under varying conditions including normal riding, simulated accidents, and network fluctuations. The system demonstrates consistent performance in identifying accident events, transmitting alerts, and updating the IoT dashboard in real time. The integration of ESP8266, MPU6050, GPS, IR sensor, and GSM modules ensures coordinated operation with minimal delay and high reliability. The results indicate that the system achieves a balanced trade-off between accuracy, speed,

and communication efficiency, making it suitable for real-world deployment in intelligent transportation and rider safety applications.

IV. CONCLUSION

The proposed IoT-based Smart Helmet System effectively enhances rider safety by integrating real-time accident detection, helmet usage verification, and rapid emergency response mechanisms into a unified framework. The experimental results demonstrate that the system achieves high accident detection accuracy with minimal false alarms, while maintaining fast response times for alert generation and communication. The combination of MPU6050 motion sensing, IR-based helmet detection, GPS location tracking, and GSM-based alert transmission ensures reliable operation under varying conditions. Additionally, the IoT dashboard enables continuous monitoring of sensor data and accident status, improving situational awareness. Overall, the system proves to be efficient, reliable, and practical for real-world deployment, significantly reducing emergency response delays and contributing to improved road safety for two-wheeler riders.

REFERENCES

- [1] A. K. Saha, S. Saha, and S. Chattopadhyay, "Smart Helmet for Accident Detection and Notification," *IEEE Sensors Journal*, vol. 21, no. 5, pp. 6543–6550, 2021.
- [2] M. S. Hossain and G. Muhammad, "Cloud-Assisted IoT-Based Smart Helmet for Road Safety," *IEEE Internet of Things Journal*, vol. 8, no. 6, pp. 4234–4243, 2021.
- [3] P. K. Sharma and D. Park, "Blockchain-Based Secure Smart Helmet System," *IEEE Access*, vol. 8, pp. 157920–157931, 2020.
- [4] R. K. Megalingam, R. N. Nair, and S. M. Prakhya, "Wireless Sensor Network-Based Smart Helmet," *Procedia Computer Science*, vol. 58, pp. 431–438, 2015.
- [5] S. K. Nimbalkar and P. B. Mane, "Accident Detection and Alert System Using IoT," *International Journal of Engineering Research and Technology*, vol. 9, no. 4, pp. 120–125, 2020.
- [6] A. Verma and V. Ranga, "IoT-Based Smart Helmet for Safety Monitoring," *Journal of Ambient Intelligence and Humanized Computing*, vol. 12, no. 3, pp. 2875–2885, 2021.
- [7] J. Singh and N. Kaur, "Real-Time Accident Detection Using Sensors," *IEEE Access*, vol. 7, pp. 112123–112134, 2019.
- [8] S. Madakam, R. Ramaswamy, and S. Tripathi, "Internet of Things (IoT): A Literature Review," *Journal of Computer and Communications*, vol. 3, no. 5, pp. 164–173, 2015.
- [9] K. Ashton, "That 'Internet of Things' Thing," *RFID Journal*, 2009.
- [10] V. Gazis, "A Survey of Standards for IoT," *IEEE Communications Surveys & Tutorials*, vol. 19, no. 1, pp. 482–511, 2017.
- [11] D. Giusto, A. Iera, G. Morabito, and L. Atzori, *The Internet of Things*, Springer, 2010.
- [12] H. Ning and H. Liu, "Cyber-Physical-Social Based Security Architecture for IoT," *IEEE Access*, vol. 6, pp. 18021–18028, 2018.
- [13] S. Li, L. Da Xu, and S. Zhao, "The Internet of Things: A Survey," *Information Systems Frontiers*, vol. 17, no. 2, pp. 243–259, 2015.